

- Fitted to EOCR relays for Large Amp Motor Protection
 1.0 Measuring Class
 For EOCR Only

Specification

Model	2CT-100	2CT-150	2CT-200	2CT-300	2CT-400
Current Ratio	100 : 5A	150 : 5A	200 : 5A	300:5A	400 : 5A
Class	1.0	1.0	1.0	1.0	1.0
Budden	5VA	5VA	5VA	5VA	5VA
Insulation Voltage	600VAC				
Dielectric Strength	2kV				
Insulation	10M				
Mounting	Panel				



- Fitted to EOCR relays for Large Amp Motor Protection
 1.0 Measuring Class
 For EOCR Only

Specification

Model	3CT-100	3CT-150	3CT-200	3CT-300	3CT-400
Current Ratio	100 : 5A	150 : 5A	200 : 5A	300 : 5A	400 : 5A
Class	1.0	1.0	1.0	1.0	1.0
Budden	5VA	5VA	5VA	5VA	5VA
Insulation Voltage	600VAC				
Dielectric Strength	2kV				
Insulation	10M Q (500VDC Megger)				
Mounting	Panel				

Zero Phase Current Transformer



- Applicable for Ground Fault Protection Devices (EGR)
 Detect Zero Phase Current
 For EOCR Only

Specification

•				
Hole Dimension	Туре	Hole		
	ZCT - 35	35mm		
	ZCT - 80	80mm		
	ZCT - 120	120mm		
Primary GF Current		200mA		
Secondary GF Current		1.5mA		
Tolerance		±10%		
Budden		10VA		
Rated Voltage		600VAC		
Dielectric Strength		2kV		
Insulation		10M Q (500VAC Megger)		
Mounting		Panel		

SR-CT

Current Transformer



- Fitted to EOCR relays for Large Amp Motor Protection
 Satisfied with IEC Inverse Trip Characteristic
 Protection Class
 For EOCR Only

Specification

Current Ratio	Туре	Current Ratio (SR-CT)		
	SR-CT-100	100 : 5A		
	SR-CT-150	150 : 5A		
	SR-CT-200	200 : 5A		
	SR-CT-300	300 : 5A		
	SR-CT-400	400 : 5A		
Tolerance (Protection Class)		±3%(10P10 / IF=10)		
Budden		1.25VA (5VA: Measuring Class)		
Secondary Current		5A		
Insulation Voltage		600VAC		
Dielectric Strength		3kV		
Insulation		10M Q (500VDC Megger)		
Mounting		35mm DIN-Rail / Panel		